

# Vita Series Business Wallbox

Vita Series Business Wallbox prioritizes safety and efficiency, complying with UK's EVSCP & EU standards. It seamlessly integrates into any setup. Effortlessly manage your charging through the cloud platform and remote maintenance. The sleek design ensures easy installation, while Wi-Fi & Ethernet connectivity enables convenient control via the mobile app. Rest assured, the MID certified energy meter guarantees the utmost accuracy in your charging experience.

## EU & UK Standard



### Simple

- Temper glass front panel
- Robust enclosure
- Easy installation
- Vinyl branding options available

### Flexible

- Type 2 cable/Type 2 socket
- Wall-mount/ Pole-mount installation
- App operation/RFID authentication/Plug to play

### Intelligent

- Communications: Wi-Fi+4G/Wi-Fi+Ethernet
- Smart mobile App control
- 2.7" B&W information display
- OCPP 1.6 Json

### Secure & Safe

- 30mA AC+6mA DC
- Independent RCBO
- MID certified energy meter with accurate measurement



# Vita Series Business Wallbox

Datasheet	Model	AC7000-AE-44	AC7000-BE-44 AC7000-BB-44	AC022K-AE-44	AC022K-BE-44 AC022K-BB-44
Electrical Specification	Power Supply	1P+N+PE		3P+N+PE	
	Rated Voltage	230V AC		400V AC	
	Rated Current	32A		32A	
	Frequency	50/60Hz			
	Rated Power	7kW		22kW	
Basic Attributes	Product Standard	EU	BE: EU / BB: UK	EU	BE: EU / BB: UK
	Charge Connector	Type 2 Cable	Type 2 Socket	Type 2 Cable	Type 2 Socket
	Cable Length	7m(4m Optional)	/	7m(4m Optional)	/
	Enclosure	PC		Galvanized Steel+Temper Glass	
	Installation	Wall-mount/Pole-mount (Optional)			
Interactive Interface	LED Indicator	Green/Yellow/Red			
	LCD Display	2.7" Black & White LCD			
	RFID Reader	Mifare ISO/IEC 14443 A			
	Start Mode	Plug to play/RFID Card/App			
Communication	Wi-Fi & Ethernet	Standard			
	Wi-Fi & 4G	Standard			
	Bluetooth	Hardware Ready			
	OCPP	OCPP 1.6 Json			
Safety	RCD	30mA Type A + 6mA DC			
	RCBO	Type A			
	Energy Meter	MID Certified			
	Ingress Protection	IP65	IP54	IP65	IP54
	Impact Protection	IK08			
	Electrical Protection	Over current protection, Residual current protection Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over temperature protection			
	Certification	CE/CB/Pen Fault/UKCA			
	Certification Standard	IEC 61851-1:2017 EN IEC 61851-1:2019 EN IEC 61851-21-2:2021 EN IEC 61000-6-1:2019 EN IEC61000-6-2/-4: 2019 EN IEC 61000-6-3:2007+A1 EN 300 328 V2.2.2:2019 EN 300 330 V2.1.1:2017 EN 301 489-1 V2.2.3:2019 EN 301 489-3 V2.1.1:2019 EN 301 489-17 V3.2.0:2017 EN 62311:2020 BS 7671:2018+A2:2022			
	Warranty	2 Years			
	Working Environment	Operation Temperature	-30°C -+50°C		
Work Humidity		5%-95%			
Work Altitude		≤2000m			
Package	Product Dimension	356*211*136mm (H*W*D)		452*295*148mm (H*W*D)	
	Package Dimension	490*340*210mm (L*W*H)		570*390*220mm (L*W*H)	
	Net Weight	5.6kg Cable	3.2kg Socket	13.5kg	9.7kg
	Gross Weight	6.4kg Cable	4.2kg Socket	15.5kg	11.6kg
	External Package	Carton			