

Taro Series Business Wallbox

Taro Series JP EV Charger is a stylish and efficient solution suitable for both wall and column installations. It is compact, visually appealing, and easy to install, providing seamless, independent, and cost-effective charging. It is an ideal choice for passenger vehicle owners looking to maximize the benefits of time-of-use tariffs.

JP Standard



Smart Charging

- Support App
- 4.3-inch color display
- Support cloud platform
- Ongoing development of OCPP 2.0.1.

User Friendly

- Various payment methods (credit card/PayPay, etc.)
- Multiple startup methods
- Various communication methods (4G, Wi-Fi, Ethernet, Bluetooth)

Safety & Reliability

- Leakage current protection
- Over-temperature protection
- Surge protection
- Rated IK10 & IP65

Scalability

- Support load balance
- Ongoing development of ISO 15118



Taro Series Business Wallbox

Datasheet	Model	AC6000-AJ-45C3	AC6000-AJ-42C3
Electrical Specification	Power supply	L1+L2+PE	
	Rated Voltage	200V AC	
	Rated Current	30A	
	Frequency	50/60Hz	
	Rated Power	6kW	
Basic Attributes	Cable Length	5m	
	Charge Connector	PSE, Type 1	
	Measurement Accuracy	1%	
	Enclosure	PC	
	Installation	Wall-mount/Pole-mount(Optional)	
Interactive Interface	LED Indicator	Green/Yellow/Red	
	LCD Display	/	4.3" LCD
	RFID Reader	Mifare ISO/IEC 14443 A and Felica	
	Start Mode	Plug to play/RFID Card/App	
Communication	Wi-Fi & Bluetooth & Ethernet	Optional	
	Wi-Fi & Bluetooth & 4G & Ethernet	Standard	
	OCPP	OCPP 1.6 Jcon	
	RS485	Optional	
Safety	RCD	Type A+6mA DC	
	Ingress Protection	IP65	
	Impact Protection	IK10	≥IK08
	Electrical Protection	Over current protection, Residual current protection Surge protection, Over/Under voltage protection, Over temperature protection	
	Warranty	2 years	
Working Environment	Operation Temperature	-30°C ~ +50°C	
	Work Humidity	5%-95%	
	Work Altitude	≤2000m	

